# **Driftwood RH**



60" x 32" x 18" ( 1524 x 813 x 457 mm) Whirlpool Operating Gallons = 38 (Liters = 144) Gallon to Overflow = 62 (Liters = 235) Right Hand Apron

## **Colors/Finishes:**

- Biscuit
- White

# **Electrical Requirements:**

- Units with Whirlpool or Air System require one 20 AMP ground fault circuit interrupter (GFCI)
- Units with Combination Whirlpool and Air System require two 20 AMP ground fault circuit interrupter (GFCI)

# **Codes/Standards/Approvals:**


- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1, ANSI Z112.19.7, ANSI A112.19.8


#### **Standard Feature:**


- Acrylic
- · Adjustable Feet
- · Non-Textured Tub Floor
- Cannot be Undermounted

## **General Information:**

- Install according to Owner's Manual and local codes
- Any tub with Whirlpool, or Air System requires an access panel.
- Hot water supply should be 65-75% of tub capacity or greater.
- Cut Dimensions: 2" Smaller than Size of tub. It is recommended to wait for unit to arrive before cutting.
- Always consult your local plumber for recommendations as installations will vary.
- All specifications are subject to change without notice.














ALL BATHTUB DIMENSIONS ARE +/- 1/2"







Whirlpool + Air System

Whirlpool

**Air System** 

Legend:













