Marco

 $60" \times 42" \times 22"$ (1524 x 1067 x 559 mm) Whirlpool Operating Gallons = 55 (Liters = 208) Gallon to Overflow = 80 (Liters = 303) Drop-In

Colors/Finishes:

- Biscuit
- White

Electrical Requirements:

- Units with Whirlpool or Air System require one 20 AMP ground fault circuit interrupter (GFCI)
- Units with Combination Whirlpool and Air System require two 20 AMP ground fault circuit interrupter (GFCI)

Codes/Standards/Approvals:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1, ANSI Z112.19.7, ANSI A112.19.8


Standard Feature:


- Acrylic
- · Adjustable Feet
- · Non-Textured Tub Floor
- Can be Undermounted


General Information:

- Install according to Owner's Manual and local codes
- Any tub with Whirlpool, or Air System requires an access panel.
- Hot water supply should be 65-75% of tub capacity or greater.
- Cut Dimensions: 2" Smaller than Size of tub. It is recommended to wait for unit to arrive before cutting.
- Always consult your local plumber for recommendations as installations will vary.
- All specifications are subject to change without notice.













ALL BATHTUB DIMENSIONS ARE +/- 1/2"

